

	Item No	Tire Size	SW	AR	Rim	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure		Tread Depth		Weight		Road Condition	UTQG	Pattern
											in	mm	in	mm	Single		Dual		psi	kpa	32nd	mm	lbs	kg			
															lbs	kg	lbs	kg									
1	HF-PCR555	235/75R15	235	75	15	-	XL	109	H	6 1/2J	9,25	235	28,86	733	2271	1030	-	-	50	340	11,5	9	29,34	13,31	M+S	440 A A	VI-286HT
2	HF-PCR551	235/60R16	235	60	16	-	-	100	H	7J	9,45	240	27,09	688	1764	800	-	-	44	300	11,5	9	27,27	12,37	M+S	440 A A	VI-286HT
3	HF-PCR552	215/65R16	215	65	16	-	-	98	H	6 1/2J	8,70	221	27,01	686	1653	750	-	-	44	300	11,0	9	25,53	11,58	M+S	440 A A	VI-286HT
4	HF-PCR351	215/70R16	215	70	16	-	-	100	H	6 1/2J	8,71	221	27,90	708	1764	800	-	-	44	300	11,0	9	26,07	11,83	M+S	440 A A	VI-286HT
5	HF-PCR352	225/70R16	225	70	16	-	-	103	H	6 1/2J	8,98	228	28,45	722	1931	875	-	-	44	300	11,0	9	27,44	12,45	M+S	440 A A	VI-286HT
6	HF-PCR553	235/70R16	235	70	16	-	-	106	H	7J	9,45	240	28,98	736	2094	950	-	-	44	300	11,5	9	30,05	13,63	M+S	440 A A	VI-286HT
7	HF-PCR554	245/70R16	245	70	16	-	XL	111	H	7J	9,76	248	29,53	750	2403	1090	-	-	50	340	11,5	9	31,35	14,22	M+S	440 A A	VI-286HT
8	HF-PCR557	255/70R16	255	70	16	-	-	111	T	7 1/2J	10,20	260	30,10	764	2403	1090	-	-	44	300	11,5	9	33,72	15,30	M+S	440 A A	VI-286HT
9	HF-PCR558	265/70R16	265	70	16	-	-	112	H	8J	10,70	272	30,60	778	2469	1120	-	-	44	300	11,5	9	36,85	16,71	M+S	440 A A	VI-286HT
10	HF-PCR353	215/60R17	215	60	17	-	-	96	H	6 1/2J	8,71	221	27,19	690	1565	710	-	-	44	300	10,0	8	25,05	11,36	M+S	440 A A	VI-286HT
11	HF-PCR561	225/60R17	225	60	17	-	-	99	H	6 1/2J	8,98	228	27,64	702	1709	775	-	-	44	300	11,0	9	27,22	12,25	M+S	440 A A	VI-286HT
12	HF-PCR354	235/60R17	235	60	17	-	-	102	H	7J	9,46	240	28,13	714	1874	850	-	-	44	300	10,5	9	28,16	12,77	M+S	440 A A	VI-286HT
13	HF-PCR355	255/60R17	255	60	17	-	XL	100	H	7 1/2J	10,24	260	29,08	738	2337	1060	-	-	50	340	10,5	9	31,67	14,37	M+S	440 A A	VI-286HT
14	HF-PCR562	225/65R17	225	65	17	-	-	102	H	6 1/2J	8,98	228	28,50	724	1874	850	-	-	44	300	12,0	10	27,88	12,65	M+S	440 A A	VI-286HT
15	HF-PCR563	235/65R17	235	65	17	-	XL	108	H	7J	9,45	240	29,06	738	2205	1000	-	-	50	340	11,5	9	31,83	14,44	M+S	440 A A	VI-286HT
16	HF-PCR556	245/65R17	245	65	17	-	XL	111	H	7J	9,80	248	29,50	750	2403	1090	-	-	50	340	11,5	9	32,67	14,82	M+S	440 A A	VI-286HT
17	HF-PCR356	255/65R17	255	65	17	-	-	110	H	7 1/2J	10,24	260	30,10	764	2337	1060	-	-	44	300	11,5	9	33,19	15,06	M+S	440 A A	VI-286HT
18	HF-PCR564	265/65R17	265	65	17	-	-	112	H	8J	10,71	272	30,55	776	2469	1120	-	-	44	300	11,5	9	34,05	15,45	M+S	440 A A	VI-286HT
19	HF-PCR559	245/70R17	245	70	17	-	-	110	T	7J	9,80	248	30,60	776	2337	1060	-	-	44	300	11,5	9	34,02	15,43	M+S	440 A A	VI-286HT
20	HF-PCR560	265/70R17	265	70	17	-	-	115	T	8J	10,70	272	31,70	804	2679	1215	-	-	44	300	11,5	9	37,93	17,20	M+S	440 A A	VI-286HT
21	HF-LT575	31X10.50R15LT	31	10,5	15	6	C	109	R	8 1/2J	10,59	269	30,51	775	2270	1030	-	-	50	350	13,5	11	38,89	17,64	M+S	-	VI-286HT
22	HF-LT577	LT235/75R15	235	75	15	6	C	104/101	R	6 1/2J	9,29	236	28,90	734	1985	900	1820	825	50	350	13,5	11	34,06	15,45	M+S	-	VI-286HT
23	HF-LT578	LT225/75R16	225	75	16	10	E	115/112	S	6J	8,78	223	29,29	744	2680	1215	2470	1120	80	550	13,5	11	34,76	15,77	M+S	-	VI-286HT
24	HF-LT579	LT245/75R16	245	75	16	10	E	120/116	S	7J	9,76	248	30,47	774	3042	1380	2778	1260	80	550	13,5	11	41,01	18,60	M+S	-	VI-286HT
25	HF-LT580	LT265/75R16	265	75	16	10	E	123/120	R	7 1/2J	10,50	267	31,65	804	3415	1550	3085	1400	80	550	13,5	11	43,50	19,73	M+S	-	VI-286HT
26	HF-LT583	LT215/85R16	215	85	16	10	E	115/112	R	6J	8,5	216	30,4	772	2680	1215	2470	1120	80	550	13,5	11	36,60	16,6	M+S	-	VI-286HT
27	HF-LT582	LT235/85R16	235	85	16	10	E	120/116	R	6 1/2J	9,25	235	31,73	806	3042	1380	2778	1260	80	550	13,5	11	39,83	18,07	M+S	-	VI-286HT
28	HF-LT576	LT265/70R17	265	70	17	10	E	121/118	S	8J	10,70	272	31,65	804	3195	1450	2910	1320	80	550	13,5	11	44,97	20,40	M+S	-	VI-286HT
29	HF-LT581	LT245/75R17	245	75	17	10	E	121/118	S	7J	9,76	248	31,50	800	3195	1450	2910	1320	80	550	13,5	11	43,28	19,63	M+S	-	VI-286HT



VI-286AT

	Item No	Tire Size	SW	AR	Rim	PR	LR	LI	SR	Rim	S.W.		O.D.		Max. Load				Max Pressure		Tread Depth		Weight		Road Condition	UTQG	Pattern
											in	mm	in	mm	Single		Dual		psi	kpa	32nd	mm	lbs	kg			
															lbs	kg	lbs	kg									
1	HF-LT558	31x10.50R15LT	31	10,5	15	6	C	109	R	8 1/2J	10,6	268	30,5	775	2270	1030	-	-	50	350	16	13	39,57	17,95	M+S	-	VI-286AT
2	HF-LT591	LT215/75R15	215	75	15	6	C	100/97	S	6J	8,5	216	27,7	703	1765	800	1610	730	50	350	16	13	30,13	13,67	M+S	-	VI-286AT
3	HF-LT566	LT235/75R15	235	75	15	6	C	104/101	R	6 1/2J	9,3	235	28,9	733	1985	900	1820	825	50	350	16	13	34,74	15,76	M+S	-	VI-286AT
4	HF-LT559	LT215/85R16	215	85	16	10	E	115/112	R	6J	8,5	216	30,4	772	2680	1215	2470	1120	80	550	16	13	38,16	17,31	M+S	-	VI-286AT
5	HF-LT561	LT235/85R16	235	85	16	10	E	120/116	R	6 1/2J	9,3	235	31,7	806	3042	1380	2778	1260	80	550	16	13	43,45	19,71	M+S	-	VI-286AT
6	HF-LT560	LT225/75R16	225	75	16	10	E	115/112	S	6J	8,8	223	29,3	744	2680	1215	2470	1120	80	550	16	13	36,27	16,45	M+S	-	VI-286AT
7	HF-LT562	LT245/75R16	245	75	16	10	E	120/116	S	7J	9,8	248	30,5	774	3042	1380	2778	1260	80	550	16	13	41,56	18,85	M+S	-	VI-286AT
8	HF-LT563	LT265/75R16	265	75	16	10	E	123/120	R	7 1/2J	10,5	267	31,7	804	3415	1550	3085	1400	80	550	16	13	46,08	20,9	M+S	-	VI-286AT
9	HF-LT584	LT285/75R16	285	75	16	10	E	126/123	R	8J	11,3	286	32,8	834	3750	1700	3415	1550	80	550	16	13	51,24	23,25	M+S	-	VI-286AT
10	HF-LT564	LT245/75R17	245	75	17	10	E	121/118	S	7J	9,8	248	31,5	800	3195	1450	2910	1320	80	550	16	13	43,98	19,95	M+S	-	VI-286AT
11	HF-LT565	LT265/70R17	265	70	17	10	E	121/118	S	8J	10,6	272	31,7	804	3195	1450	2910	1320	80	550	16	13	46,52	21,1	M+S	-	VI-286AT
12	HF-LT585	LT285/70R17	285	70	17	10	E	121/118	R	8 1/2J	11,5	292	32,8	832	3195	1450	2910	1320	80	550	16	13	51,71	23,46	M+S	-	VI-286AT
13		215/75R15	215	75	15	-	-	100	S	6J	8,50394	216	27,6772	703	1764	800	-	-	44	300	12	10	26,01	11,8	M+S	460AB	VI-286AT
14	HF-PCR565	235/75R15	235	75	15	XL	-	109	S	6 1/2J	9,3	235	28,9	733	2271	1030	-	-	50	340	13	10	30,79	13,97	M+S	460AB	VI-286AT
15	HF-PCR566	235/70R16	235	70	16	-	-	106	T	7J	9,4	240	29,0	736	2094	950	-	-	44	300	13	10	31,47	14,28	M+S	460AB	VI-286AT
16	HF-PCR567	245/70R16	245	70	16	-	-	107	T	7J	9,8	248	29,5	750	2150	975	-	-	44	300	13	10	32,8	14,88	M+S	460AB	VI-286AT
17	HF-PCR568	255/70R16	255	70	16	-	-	111	T	7 1/2J	10,2	260	30,1	764	2403	1090	-	-	44	300	13	10	34,14	15,49	M+S	460AB	VI-286AT
18	HF-PCR569	265/70R16	265	70	16	-	-	112	T	8J	10,7	272	30,6	778	2469	1120	-	-	44	300	13	10	35,95	16,31	M+S	460AB	VI-286AT
19	HF-PCR570	245/75R16	245	75	16	-	-	111	S	7J	9,8	248	30,5	774	2403	1090	-	-	44	300	13	10	34,07	15,46	M+S	460AB	VI-286AT
20	HF-PCR571	265/75R16	265	75	16	-	-	116	S	7 1/2J	10,5	267	31,7	804	2755	1250	-	-	44	300	13	10	38,24	17,35	M+S	460AB	VI-286AT
21	HF-PCR572	245/65R17	245	65	17	-	-	107	T	7J	9,8	248	29,5	750	2150	975	-	-	44	300	13	10	32,66	14,82	M+S	460AB	VI-286AT
22	HF-PCR573	265/65R17	265	65	17	-	-	112	T	8J	10,7	272	30,6	776	2469	1120	-	-	44	300	13	10	36,82	16,7	M+S	460AB	VI-286AT
23	HF-PCR574	245/70R17	245	70	17	-	-	110	T	7J	9,8	248	30,6	776	2337	1060	-	-	44	300	13	10	34,43	15,62	M+S	460AB	VI-286AT
24	HF-PCR575	265/70R17	265	70	17	-	-	115	T	8J	10,7	272	31,7	804	2679	1215	-	-	44	300	13	10	37,53	17,03	M+S	460AB	VI-286AT
25	HF-PCR576	P285/70R17	285	70	17	-	-	117	T	8 1/2J	11,5	292	32,8	832	2833	1285	-	-	44	300	13	10	41,1	18,65	M+S	460AB	VI-286AT